

FS-C5030N Print System

Product Overview

This 26ppm Letter or Legal size full-color ECOSYS workgroup printer is capable of imaging at a multi-bit 600dpi for crisp, corporate documents. In addition, the fast PowerPC750FX 600MHz CPU processes documents quickly for maximum productivity and minimum wait time. With a small footprint and fast output speed, the FS-C5030N also makes an excellent Network Printer.



Fast Affordable Monochrome Printing

Technology

- ◆ **Type:** Desktop Full-Color/Monochrome Printers
- ◆ **Imaging System:** 4 Drum Tandem
- ◆ **Color Technology:** Advanced Beam Array
- ◆ **Primary Transfer:** Intermediate Transfer Belt
- ◆ **Secondary Transfer:** Roller
- ◆ **Fusing:** Oil Less Heat/Pressure
- ◆ **Controller:** PowerPC750FX - 600Mhz
- ◆ **Print Resolution:** Multi Bit 600 DPI
(2 and 4 bit modes)
- ◆ **Gradation Levels:** 256
- ◆ **Service:** 200K MK-522 Maintenance Kit
Includes: Drum, Developer Kit,
Transfer Unit, Feed Unit,
Fuser Kit, Two Ozone Filters, Roller
Feed Set
- ◆ **C, M, Y, K Toner Cartridge Yield:**
8K at 5% Coverage
- ◆ **Toner Type:** Polymerized
- ◆ **HDD:** Optional 20GB
- ◆ **Maximum Monthly Volume:** 100K

Memory Management

- ◆ Optional HDD
- ◆ 128MB RAM (1024MB Max with 100 pin DDR DIMMs)
- ◆ One Compact Flash Card Slot (Type 1)
- ◆ One KUIO-LV Slot

Speeds

- ◆ Warm up: 60 Seconds

FS-C5030N	
FPOt Color/Mono	12 Sec
Letter (Color/Mono)	26/26 PPM
Legal (Color/Mono)	21/21 PPM
Thick (Color/Mono)	12/12 PPM
OHP (Color/Mono)	12/12 PPM
Duplex (letter)	24 PPM
Duplex Letter Efficiency	92%
Duplex (legal)	20 PPM
Duplex Legal Efficiency	95%

Connectivity & Interface

- ◆ Std. 10/100 BaseTX
- ◆ Std. Hi-Speed USB 2.0
- ◆ Std. Bi-Directional Parallel
(IEEE 1284 Nibble/ECP mode)
- ◆ Std. KUIO-LV (one slot for HDD or one of the following:)
 - ◆ Opt. IB-22 IEEE 802.11b (Wireless)
 - ◆ Opt. IB-20 10/100 BaseTX, 10Base2
 - ◆ Opt. IB-11 Serial

Paper Handling

- ◆ **Std. 500 Sheet Paper Drawer**
 - ◆ Paper Size: Letter, Legal, A4, A5, B5
 - ◆ Paper Weights: 16lb - 28lb Bond
 - ◆ Paper Types: Plain, Recycled, Thick
- ◆ **Std. 100 Sheet Multi-Purpose Tray**
 - ◆ Paper Size: Letter, Legal, A4, A5, B5
Custom: 2.8" x 5.8" - 8.5" x 14"
 - ◆ Paper Weights: 16lb - 24lb Bond, 110lb Index
 - ◆ Paper Types: Plain, Recycled, Transparencies, Adhesive-Backed Labels, Envelopes, Cardstock, PostCards
- ◆ **Std./Max. Paper Supply:** 600/2,100 Sheets
- ◆ **Std./Max. Paper Sources:** 2/5 Drawers
- ◆ **Opt. 500 Sheet Paper Drawer (Up to 3)**
 - ◆ Paper Size: Letter, Legal, Custom
 - ◆ Paper Weights: 16 to 28lb Bond
- ◆ **Opt. Automatic Duplex Unit**
 - ◆ Paper Weights: 16 to 28lb Bond
- ◆ **Opt. Envelope Feeder**
 - ◆ 1.5" or 40mm height capacity
- ◆ **Face-Up Tray**
 - ◆ 250 sheet for Printer
 - ◆ 100 sheets for Duplexer

Connectivity & Interface

- ◆ Std. 10/100 BaseTX
- ◆ Std. Hi-Speed USB 2.0
- ◆ Std. Bi-Directional Parallel (IEEE 1284 Nibble/ECP mode)
- ◆ Std. KUIO-LV (one slot for HDD or one of the following:)
 - ◆ Opt. IB-22 IEEE 802.11b (Wireless)
 - ◆ Opt. IB-20 10/100 BaseTX, 10Base2
 - ◆ Opt. IB-11 Serial

Print Description Languages

- ◆ KPDL3 (Postscript 3 Emulation)
- ◆ PCL 6 (PCL 5c/PCL XL)
- ◆ PRESCRIBE

Fonts

- ◆ 136 KPDL PostScript
- ◆ 80 PCL 5c/PCL XL Outlines
- ◆ 1 Bitmap

Compatibility

- ◆ Windows OS: 9x/Me/2000/XP
- ◆ Novell: Novell Netware 3.x/4.x/5.x/6.x
- ◆ Mac OS: 8.x/9.x/10.x
- ◆ UNIX: Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)

Supported Protocols

- ◆ TCP/IP
- ◆ IPX.SPX
- ◆ AppleTalk
- ◆ NetBEUI

Driver

- ◆ KX Driver for Windows
- ◆ PPD for Mac
- ◆ PPD for CUPS (Linux/Unix)
- ◆ Certified Uni Driver

KM-NET Solution

- ◆ KM-NET Viewer Web Edition
- ◆ KM-NET Viewer
- ◆ KM-NET Client
- ◆ KM-NET PDF Direct Print
- ◆ Network Advanced Set-Up Utilities
- ◆ PRESCRIBE Utilities

Yields

- ◆ Starter Toner: 4K @ 5% Coverage for C, M, Y, K
- ◆ C, M, Y, K Toner: 8K @ 5% Coverage
- ◆ Maintenance Kit: 200K

Other

- ◆ W x D x H: 13.6" x 18.5" x 15.2"
- ◆ Weight: 50.3 lbs
- ◆ Power Requirements: 120 V, 60 Hz, 9.4 A
- ◆ Energy Star Compliant
- ◆ Operating Noise Level: 53 dB

Options

- ◆ Memory: 64, 128, 256, 512MB x 2 slots (DDR DIMMs)
- ◆ Compact Flash Card (1 slot)
- ◆ Hard Disk Drive
- ◆ Interface Boards: IB-11, IB-20, IB-22
- ◆ Add up to three 500 Sheet Paper Drawers (PF-60)
- ◆ Automatic Duplex Unit (DU-301)
- ◆ Envelope Feeder (EF-60)
- ◆ Face-Up Tray (PT-301)



4.11.05

